

Model IQ 50

Deluxe slimline telephone with "light"

Feature List

- Backlit keypad
- Large keys for easy use
- Built-in message waiting and ringer indicator lamp*
- Keypad and Line Reset button located on the handset
- 100 mS PBX Recall and Pause/Redial keys
- Tone dialling
- Ringer volume control and ringer light
- Wall Bracket included
- Three (3) Year parts and labour warranty
- Message waiting light built-in to suit many popular PABXs and optional add-ons to suit many others
- Hearing aid compatible
- Individual serial no. on each unit
- 'Tropicguard' protection for humid conditions such as hotel bathrooms
- Noise cancelling handset microphone



Specifications of Interquartz IQ 50	
Dial mode	Tone (DTMF) signaling system conforms to CCITT Recommendation Q.23: Frequency Deviation <1.5%; Total Distortion Product <10%; Digit (Tone) Duration >85msec.; Interdigit Pause >85 msec.
PBX Recall	100 milliseconds Timed Break
Message Waiting light	80 - 120VDC either constant or flashing
Ringer Lamp	Neon tube
Dimensions	Width: 68mm; Length: 222mm; Height: 73mm
Ringer	Electronic, with Hi/Lo/Off settings; 80dBA minimum at a distance of 30 cm.
Weight	The weight of the unit is 0.6 kg, approximately
Line cord and Plug	3m RJ12 to RJ45 with optional 603, RJ11 or RJ12
Wall mount kit	Included
Operating Temp and Humidity	Temperature : 0°C - 40°C; Humidity : 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Colour	Granite Grey - ABS plastic

* Built-in message waiting lamp is compatible with Ericsson BP250 (except IQ 50) and most later systems from Alcatel, Exicom, Fujitsu, NEC, Nortel, Nitsuko, Samsung and Hybrex. AT&T, Lucent, GPT ISDX, GEC Siemens Hicom, Panasonic, Ericsson MD110 and some Hybrex message waiting lamps are optional extras.