

## Model IQ 9826

*Slimline telephone for office, home or hotel*

### Feature List

- Tone dialling
- Ringer volume control
- Redial and Pause functions
- Dialess version available for hotline, hotel lobby or information booth application
- Very durable yet lightweight telephone
- Full Three (3) Year parts and labour warranty
- Satin textured finish
- Wall Mounting and also suitable for desk use
- Optional Screen Printing of logos or other information
- Hearing aid compatible
- Individual serial no. on each unit
- 'Tropicguard' protection for humid conditions such as hotel bathrooms
- Noise cancelling handset microphone



Specifications of Interquartz IQ 9826	
Dial mode	Tone (DTMF) signalling system conforms to CCITT Recommendation Q.23: Frequency Deviation <1%; Total Distortion Product <10%; Digit (Tone) Duration >100msec.; Interdigit Pause >100msec.
PBXRecall	100 milliseconds Timed Break
Power Source	Line powered.
Dimensions	Width: 68mm; Length: 222mm; Height: 73mm
Weight	The weight of the unit is 0.6 kg, approximately
Ringer	Electronic, with Hi/Lo/Off settings; 80dBA minimum at a distance of 30 cm.
Line cord and Plug	3m RJ12 to RJ45 with optional 603, RJ11 or RJ12
Wall mount kit	Wall Mount Kit No.1 (Order separately)
Operating Temp and Humidity	Temperature : 0°C - 40°C; Humidity : 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Colour	Granite Grey - ABS plastic